

The DataSafe® HX range of valve regulated lead acid batteries has been designed to offer superior solutions for the Uninterruptible Power Supply (UPS) and Information Technology markets. DataSafe HX batteries are the ideal source of power to protect vital systems and incorporates select design features that maximise reliability

12HX540-FR 31.0 6.1 Charging Current The recommended charging method for DataSafe HX batteries is current limited, constant voltage charging. Refer to Table 1 for the current limits for each battery model. State of Charge The battery state of ...

EnerSys DataSafe 12HX540-FR valve regulated lead acid batteries have been designed to offer superior solutions for the Information Technology and Uninterruptible Power Supply markets. DataSafe HX batteries are the ideal source of power to protect vital systems. DataSafe HX batteries incorporate select design features that maximize reliability while ensuring superior ...

DataSafe HX Battery Type 5 101520 30 45 60 Standby Time (Minutes) DataSafe HX+ Battery Type 5 101520 30 45 60 Standby Time (Minutes) ... 12HX540 897.5674.8531.7438.5235.9186.2 326.3 . Constant Power Discharge Performance Data Constant Power (Watts per cell) to ...

12HX540 10.0 5.0 16HX550F 12.0 6.0 16HX800F 20.0 10.0 16HX925F 23.0 11.5 DataSafe® HX Maximum charging Max recommended rms Battery current (A) value of the alternating Type component (A) Table 1 State of charge Voltage 100% 2.12 to 2.14 V/Cell 80% 2.09 to 2.11 V/Cell 60% 2.05 to 2.08 V/Cell 40% 2.01 to 2.04 V/Cell 20% 1.97 to 2.00 V/Cell Table 2

The DataSafe ® HX top terminal ... 12HX540-FR 12 123 540 13.3 338 6.8 173 10.7 272 106.0 48.1 4775 2.6 1 D 1.70 6.44 18.41 8.35 2 AM-HX-RS AA March 2018. Battery Range Summary Constant Power Discharge (Watts per Cell) to 1.75Vpc at 77°F (25°C) Constant Power Discharge (Watts per Cell) to 1.70Vpc at 77°F (25°C) ...

AM-HX-IOM AA December 2018 3 For cabinet installations, reference DataSafe ® HX Battery Cabinet Systems Range Summary (AM-DSCAB-RS). If provided, intercell connector covers should be installed after completing the

12°F (5°C) 12HX205-FR - 12HX540-FR: -22°F (-30°C) to 122°F (50°C) Float charging voltage 2.25-2.28 Volts per cell at 77°F (25°C) DataSafe ® HX top terminal batteries can be safely recharged at high current rates. DataSafe HX top terminal batteries can be stored for up to six months at 77°F (25°C) before a freshening charge is ...

ENERSYS DATASAFE 12HX540-FR BATTERIES. Power Storage Solutions is a premier platinum stocking Distributor for the Datasafe 12HX540 batteries. We maintain the batteries in a climate controlled environment, then charge and test each unit prior to shipment. The DataSafe HX top terminal battery range of Valve Regulated Lead Acid (VRLA ...

BATERIAS DATASAFE-12HX540FR 12V 123Ah. Las Baterias DataSafe cuentan con tecnologa de plomo cido regulado por vlvula (vrla), las baterias DataSafe HX ofrecen soluciones superiores para una amplia gama de sistemas de alimentaci3n ininterrumpida (ups) y aplicaciones de TI. las baterias combinan varias caracteristicas de diseo selectas para ...

Energys DataSafe 12HX540-FR Battery - 12V 540W *Minimum Order Required On This Item *Ships Factory Direct - Non-Cancellable - Non-Returnable. Voltage: 12 Volts. Capacity: 540W. Chemistry: AGM - Sealed Lead. Dimensions: L 13.30" x W 6.80" x H 10.70"; Terminals: M6 Insert. Product Videos. Custom Field.

View and Download EnerSys DataSafe 12HX205-FR installation, operation and maintenance instructions online. DataSafe 12HX205-FR camera accessories pdf manual download. Also for: Datasafe hx series, Datasafe 12hx300-fr, Datasafe 12hx330-fr, ...

The DataSafe HX 12HX50's front terminal scales to larger Kva systems, including 550, 800, and 925 watts per cell (WPC). All DataSafe HX batteries have a 10-year life expectancy and arrive at 100% initial battery capacity. Use in conjunction with a flame-repellant case and cover and a Front Terminal DataSafe cabinet for highest energy density.

DataSafe HX batteries are the ideal source of power ... 12HX205 - 12HX540: -30°C to +50°C Recommended: 20°C to 25°C o Up to six months shelf life (at 25°C) Standards ... Switzerland. EnerSys Asia. 152 Beach Road. Gateway East Building #11-08

Buy 12HX540-FR - ENERSYS - DATASAFE Valve-Regulated Lead Acid Battery. Newark Electronics offers fast quotes, same day dispatch, fast delivery, wide inventory, datasheets & technical support.

Energys DataSafe 12HX540-FR valve regulated lead acid batteries have been designed to offer superior solutions for the Information Technology and Uninterruptible Power Supply markets. DataSafe HX batteries are the ideal source of power to protect vital systems. DataSafe HX batteries incorporate select design features that maximize reliability ...

Web: <https://www.sailesindustrialmachinery.co.za>